

ARCTIC™ 6% AFFF FOAM CONCENTRATE

# CONCENTRATES



## Description

ARCTIC™ 6% AFFF foam concentrate from SOLBERG® is a synthetic foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 6% solution. ARCTIC 6% AFFF foam provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, salt and brackish water.

## Application

ARCTIC 6% AFFF foam concentrate can be applied to Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapors. Foam discharge devices such as air aspirating, as well as, non-air aspirating equipment can be used to obtain maximum results. The product is mixed 6 parts foam concentrate to 94 parts water. It may also be used as a 6% pre-mix solution. ARCTIC 6% AFFF foam is compatible with most powder (dry chemical) agents.

## Performance

### Fire Performance

ARCTIC 6% AFFF foam concentrate has been tested to and meets the fire performance test criteria of Underwriters Laboratories, Inc. (UL) Standard 162 and Underwriters' Laboratories of Canada (ULC) Standard S564.

### Foam Proportioning

ARCTIC 6% AFFF foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

### Storage

The storage temperature range for ARCTIC 6% AFFF foam concentrate is 35 °F to 120 °F (1.7 °C to 49 °C).

When stored in original containers or in manufacturer recommended

## Typical Physical Properties at 77 °F (25 °C)

Appearance:	Clear, light yellow liquid
Freezing Point:	32 °F (0 °C) <i>(No quality loss after thawing)</i>
Maximum storage temp:	120 °F (49 °C)
pH:	7.0 - 8.5
Refractive index:	1.3400 - 1.3450
Specific gravity:	1.005 - 1.025
Viscosity:	1.7 - 3.7 cSt*
Sediments:	<0.05%

\* Cannon-Fenske Viscometer

equipment and within the specified temperature range, the shelf life is 20 years.

## Compatibility

ARCTIC 6% AFFF foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Solberg Technical Services.

*Solberg is a member of THE AMEREX GROUP, an alliance of independent companies with a singular purpose: revolutionize the course of fire suppression technology with safer, more effective, and more sustainable solutions. Together, we are Moving Industries Forward by Redefining Fire Suppression. [www.solbergfoam.com](http://www.solbergfoam.com)*



**Materials of Construction Compatibility**

ARCTIC 6% AFFF foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Solberg Technical Services.

**Inspection**

ARCTIC 6% AFFF foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

**Environmental Information**

ARCTIC 6% AFFF foam concentrate is formulated with C<sub>6</sub> fluorosurfactants and complies with the United States Environmental Protection Agency (USEPA) 2010/2015 PFOA Stewardship Program. SOLBERG ARCTIC foam concentrates do not contain PFOS.

**Certifications**

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters and finished product's fire performance. A Certificate of Analysis (CoA) is available for every batch.

ARCTIC 6% AFFF foam concentrate is Underwriters Laboratories, Inc. Listed in accordance with UL 162 (Standard for Safety for Foam Equipment and Liquid Concentrates) and Underwriters' Laboratories of Canada Listed (Standard for Category 1 Foam Liquid Concentrates ULC S564).

**Ordering Information**

ARCTIC 6% AFFF foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	APPROXIMATE SHIPPING WEIGHT	APPROXIMATE CUBE
20246	ARCTIC 6% AFFF, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft <sup>3</sup> (0.04 m <sup>3</sup> )
20247	ARCTIC 6% AFFF, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft <sup>3</sup> (0.33 m <sup>3</sup> )
20248	ARCTIC 6% AFFF, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft <sup>3</sup> (1.42 m <sup>3</sup> )
20249	ARCTIC 6% AFFF, bulk	Call Customer Services	

SOLBERGFOAM.COM

FORM NUMBER F-2015016-2

COPYRIGHT © 2014. ALL RIGHTS RESERVED. SOLBERG® AND ARCTIC™ ARE TRADEMARKS OF THE SOLBERG COMPANY OR ITS AFFILIATES.

**AMERICAS**  
THE SOLBERG COMPANY  
1520 Brookfield Avenue  
Green Bay, WI 54313  
USA  
Tel: +1 920 593 9445

**EMEA**  
SOLBERG SCANDINAVIAN AS  
Radøyvegen 721 - Olsvollstranda  
N-5938 Sæbøvågen  
Norway  
Tel: +47 56 34 97 00

**ASIA-PACIFIC**  
SOLBERG ASIA PACIFIC PTY LTD  
3 Charles Street  
St. Marys NSW 2760  
Australia  
Tel: +61 2 9673 5300