

ARCTIC™ 650, 3% AFFF FOAM CONCENTRATE

CONCENTRATES



Description

ARCTIC™ 650, 3% AFFF foam concentrate from SOLBERG® is a synthetic foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires at 3% solution. ARCTIC 650, 3% AFFF foam concentrate provides rapid extinguishment and excellent burn back characteristics and can be used with fresh, sea and brackish water.

Application

ARCTIC 650, 3% AFFF foam concentrate can be applied to Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam can be used to prevent re-ignition of a liquid spill and control hazardous vapors. Foam discharge devices such as non-air aspirating, as well as, air aspirating equipment, including standard fire sprinkler heads, can be used to obtain maximum results. The product is mixed 3 parts foam concentrate to 97 parts water. It may also be used as a 3% pre-mix solution. ARCTIC 650, 3% AFFF foam concentrate is compatible with most powder (dry chemical) agents.

Performance

Fire Performance

ARCTIC 650, 3% AFFF foam concentrate has been tested to and meets the fire performance test criteria of European Standard EN 1568, Part 3 (latest edition).

Foam Proportioning

ARCTIC 650, 3% AFFF foam concentrate can be proportioned at the proper foam solution percentage using most common proportioning devices such as:

- Eductors
- Inline balance pressure proportioners
- Ratio controllers
- Self-inducting nozzles

Storage

The minimum and maximum temperature for ARCTIC 650, 3% AFFF foam concentrate is 35 °F to 120 °F (1.7 °C to 49 °C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is 20 years.

Typical Physical Properties at 77 °F (25 °C)

Appearance:	Clear, light yellow liquid
Freezing Point:	28.4 °F (-2 °C) <i>(No quality loss after thawing)</i>
Maximum storage temp:	120 °F (49 °C)
pH:	7.0 - 8.0
Refractive index:	1.3439
Specific gravity:	1.02
Viscosity:	1.8 cSt
Sediments:	None

Compatibility

ARCTIC 650, 3% AFFF foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing of foam concentrates, consult Solberg Technical Services.

Materials of

Construction Compatibility

ARCTIC 650, 3% AFFF foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about material compatibility, consult Solberg Technical Services.

SOLBERG is a member of PERIMETER SOLUTIONS, a global producer of leading fire retardant, gel and foam brands with a singular purpose: revolutionize the course of fire suppression technology with safer, more effective and more sustainable solutions. Together, we are Moving Industries Forward by Redefining Fire Suppression. www.solbergfoam.com



Inspection

ARCTIC 650, 3% AFFF foam concentrate or pre-mix solutions should be inspected annually per National Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

Environmental Information

ARCTIC 650, 3% AFFF foam concentrate complies with the United States Environmental Protection Agency (USEPA) Stewardship Program—2015 Requirements.

Approvals & Listings

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze

the foam’s physical parameters and finished product’s fire performance. A Certificate of Analysis (CoA) is issued with every batch.

ARCTIC 650, 3% AFFF foam concentrate meets the fire performance requirements of European CEN EN 1568, Part 3 Standard as witnessed by DET NORSKE VERITAS (DNV).

Ordering Information

ARCTIC 650 3% AFFF foam concentrate is available in pails, drums, totes and bulk quantities.

DESCRIPTION	APPROXIMATE WEIGHT SHIPPING	APPROXIMATE CUBE
ARCTIC 650, 3% AFFF, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
ARCTIC 650, 3% AFFF, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
ARCTIC 650, 3% AFFF, 275 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
ARCTIC 650, 3% AFFF, bulk	Call Customer Services	



NOTICE: Perimeter Solutions makes no representations or warranties as to the completeness or accuracy of the information included herein. The information contained herein is not intended to provide regulatory, legal or expert advice relating to the products, its application or uses. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any industrial property or intellectual property rights, and Perimeter Solutions makes no representation or warranty, express or implied, that the use thereof will not infringe on any industrial property or intellectual property rights. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.

SOLBERGFOAM.COM

FORM NUMBER F-2012032-2

COPYRIGHT © 2013. ALL RIGHTS RESERVED. SOLBERG® AND ARCTIC™ ARE TRADEMARKS OF PERIMETER SOLUTIONS LP OR ITS AFFILIATES.

AMERICAS
PERIMETER SOLUTIONS, LP
1520 Brookfield Avenue
Green Bay, WI 54313
USA
Tel: +1 920 593 9445

EMEA
PERIMETER SOLUTIONS, LP
Polígono de Baiña, Parcela 23
33682 Mieres (Asturias)
Spain
Tel: +34 985 24 29 45

ASIA PACIFIC
PERIMETER SOLUTIONS, LP
3 Charles Street
St. Marys NSW 2760
Australia
Tel: +61 2 9673 5300